

Checklist for Designing or Reading a Model

The MiniZinc Language

Modelling

Set Variables &Constraints

Modelling Checklist

- Each array index occurs twice in the comment on the array's declaration;
 array[I,J] of ...: X; % X[i,j] = the ... i ... j
- 2 Each array index range either starts from 1 or is an enum, for clarity
- 3 Beware of decision variables declared without tight domains
- 4 No decision variable has a non-inlined equality constraint
- **5** No decision variable of type opt au is declared explicitly (in this course)
- 6 No sum | forall (i in 1..x) with a decision variable x is used
- 7 No equality constraints are pushed into an if then else expression
- **8** Beware of where θ and if θ with test θ on decision variables
- Beware of explicit (<->) and implicit (bool2int (...)) reification
- Beware of logical negation and disjunction: not, $\/$, exists, xor, xorall, if θ then ϕ else ψ endif, <-, ->, <->
- Beware of nonlinear, pow, div, mod constraints on decision variables



Checklist for Designing or Reading a Model

Motivation

different

nvalue

cardinality

bin_packing. knapsack

cumulative. disjunctive

subcircuit lex_lesseq

regular.

table

global_

element

Checklist

12 Constraint predicates with the most specific meanings are used

Global constraints are used, instead of their definitions

14 Constraints over shared decision variables are ideally merged

15 The element predicate is not used explicitly, for readability

Functions on small sets are encoded by implicit element, if need be

Relations over small sets are encoded by regular or table, if faster than a formulation in the scope of checklist items 6 to 11 of Topic 2



Conventions of all Slides (recommended!)

The MiniZinc

Modelling

Set Variables &Constraints

Modelling Checklist

- Scalar identifiers (bool, enum items, int) start with a lowercase letter.
- Mass identifiers (array, enum, set) start with an uppercase letter.
- Arrays have self-explanatory function identifiers: a given|unknown total function $f: X \to Y$ can be modelled as array[X] of par|var Y: F.
- Index identifiers are lowercase and mnemonic: memory aid.
- Comments about the *next* line end in ":", like line 2 in the example below.

Example

```
int: nQueens; % the given number of queens
% Row[c] = the row number of the queen in column c:
array[1..nQueens] of var 1..nQueens: Row;
```

Variable Row[c] is like Row(c), denoting the function Row applied to arg. c. The array Row is *not* a variable, but an *array of* variables: it has row numbers, but calling it Rows would make Rows[c] seem to denote a *set* of rows for c!



Ideas for Debugging and Accelerating a Model

The MiniZinc Language

Modelling

Set Variables &Constraints

Modelling Checklist

- If there are no solutions (or missing solutions) to a known-to-be satisfiable instance, then:
 - Comment away constraints in order to increase the solution set and thereby find unsatisfiable constraints.
 - In the IDE or CLI, choose findMUS as the backend in order to find a minimal unsatisfiable subset (MUS) of the constraints: see Section 3.8 of the MiniZinc Handbook.
- In the IDE, choose "Run > Profile compilation" in order to see per model line the numbers of constraints and decision variables generated by its flattening, and the flattening time: if some of these numbers are extreme, then you probably ran afoul of items of the checklist on the next slide.
- In the IDE, choose "Run > Compile" in order to inspect the flat code.